

Specifications:

MODELS	Output max		Output min	
	kW	kcal / hx1000	kW	kcal / hx1000
<b>OILFLAM 15.1</b>	15.1	175	15086	6035
<b>OILFLAM 20.1</b>	233	200	93	80
<b>OILFLAM 30.1</b>	349	300	174	150
<b>OILFLAM 50.1</b>	581	500	290	250
<b>OILFLAM 80.1</b>	930	800	464	400
<b>OILFLAM 120.1</b>	1.395	1.2	682	588
<b>OILFLAM 170.1</b>	1.7	1.45	682	588
<b>OILFLAM 200.1</b>	2.093	1.96	682	588
<b>OILFLAM 300.1</b>	3	2.586	1	867,3
<b>OILFLAM 400.1</b>	3.9	3.362	1.3	1.127,5
<b>OILFLAM 500.1</b>	5	4.31	1.578	1.368,6
<b>OILFLAM 600.1</b>	5.8	5	1.795	1.556,8
<b>OILFLAM 700.1</b>	7.5	6.465	2.417	2096.27
<b>OILFLAM 800.1</b>	8.5	7.327,5	2.75	2.385,1
<b>OILFLAM 1000.1</b>	10.5	9.052	3.3	2.862,1
<b>OILFLAM 1200.1</b>	12.5	10.776	4.367	3.787,5
<b>OILFLAM 1500.1</b>	15	12.931	5	4.31
<b>OILFLAM 1800.1</b>	17	14.655	5.7	4.941